

SG9302



Номинальный ток I_n	Типовое обозначение	Код для заказа	Упаковка (шт.)
3+N полюсные			
6 A	PL7-B6/3N-RU	108547	3/30
10 A	PL7-B10/3N-RU	108548	3/30
13 A	PL7-B13/3N-RU	108549	3/30
16 A	PL7-B16/3N-RU	108550	3/30
20 A	PL7-B20/3N-RU	108551	3/30
25 A	PL7-B25/3N-RU	108552	3/30
32 A	PL7-B32/3N-RU	108553	3/30
40 A	PL7-B40/3N-RU	108554	3/30
50 A	PL7-B50/3N-RU	108555	3/30
63 A	PL7-B63/3N-RU	108556	3/30

Характеристика C, отключающая способность 10 кА

- Использование для защиты цепей питания и освещения со средним уровнем пускового тока

SG7502



Номинальный ток I_n [A]	Типовое обозначение	Код для заказа	Упаковка (шт.)
1-полюсные			
0,16 A	PL7-C0,16/1-RU	108427	12/120
0,25 A	PL7-C0,25/1-RU	108428	12/120
0,5 A	PL7-C0,5/1-RU	108429	12/120
0,75 A	PL7-C0,75/1-RU	108430	12/120
1 A	PL7-C1/1-RU	108431	12/120
1,6 A	PL7-C1,6/1-RU	108432	12/120
2 A	PL7-C2/1-RU	108433	12/120
4 A	PL7-C4/1-RU	108434	12/120
6 A	PL7-C6/1-RU	108435	12/120
10 A	PL7-C10/1-RU	108436	12/120
13 A	PL7-C13/1-RU	108437	12/120
16 A	PL7-C16/1-RU	108438	12/120
20 A	PL7-C20/1-RU	108439	12/120
25 A	PL7-C25/1-RU	108440	12/120
32 A	PL7-C32/1-RU	108441	12/120
40 A	PL7-C40/1-RU	108442	12/120
50 A	PL7-C50/1-RU	108443	12/120
63 A	PL7-C63/1-RU	108444	12/120

SG14002



1+N полюсные			
2 A	PL7-C2/1N-RU	108530	8/80
4 A	PL7-C4/1N-RU	108531	8/80
6 A	PL7-C6/1N-RU	108532	8/80
10 A	PL7-C10/1N-RU	108533	8/80
13 A	PL7-C13/1N-RU	108534	8/80
16 A	PL7-C16/1N-RU	108535	8/80
20 A	PL7-C20/1N-RU	108536	8/80
25 A	PL7-C25/1N-RU	108537	8/80
32 A	PL7-C32/1N-RU	108538	8/80

SG8702



2-х полюсные			
0,5 A	PL7-C0,5/2-RU	108465	6/60
1 A	PL7-C1/2-RU	108466	6/60
2 A	PL7-C2/2-RU	108467	6/60
4 A	PL7-C4/2-RU	108468	6/60
6 A	PL7-C6/2-RU	108469	6/60
10 A	PL7-C10/2-RU	108470	6/60
13 A	PL7-C13/2-RU	108471	6/60
16 A	PL7-C16/2-RU	108472	6/60
20 A	PL7-C20/2-RU	108473	6/60
25 A	PL7-C25/2-RU	108474	6/60
32 A	PL7-C32/2-RU	108475	6/60
40 A	PL7-C40/2-RU	108476	6/60
50 A	PL7-C50/2-RU	108477	6/60
63 A	PL7-C63/2-RU	108478	6/60