

**PZ 10 HEX**

0.14 ... 10 mm<sup>2</sup>




- ~AWG 26 ... 8
- Only one die for the whole cross-section range of 0.14 ... 10 mm<sup>2</sup>
- Side wire-end ferrule insertion with hexagon crimp shape

**PZ 10 SQR**

0.14 ... 10 mm<sup>2</sup>



- ~AWG 26 ... 8
- Only one die for the whole cross-section range of 0.14 ... 10 mm<sup>2</sup>
- Side wire-end ferrule insertion with square crimp shape



**Technical data**

Description of contact	
Type of contact	
Crimping range	mm <sup>2</sup>
Crimping range 1 (with multiple crimping positions)	-
Crimping range 2 (with multiple crimping positions)	-
Crimping range 3 (with multiple crimping positions)	-
Crimping range 4 (with multiple crimping positions)	-
Crimping range 5 (with multiple crimping positions)	-
Tool data	
Length	mm
Weight	g
Note	

Wire-end ferrules with/without plastic collars		
0.14...10		

Wire-end ferrules with/without plastic collars		
0.14...10		

**Ordering data**

Version
Note

Type	Qty.	Order No.
PZ 10 HEX	1	1445070000
PZ 10 HEX ZERT	1	1989320000

Type	Qty.	Order No.
PZ 10 SQR	1	1445080000
PZ 10 SQR ZERT	1	1989310000